SPECIFICATIONS

Model Name		4T-B60CP1X		
Operating hours		16 hours / 7 days		
Installation		Landscape / Portrait *2		
Sound output		10w x 2		
LCD panel		60 inch widescreen (152.7cm diagonal) TFT LCD		
	Max. Resolution	3840 x 2160 pixels		
	Max. Display Colours (approx.)	16.77 million colours		
	Pixel Pitch (H x V)	0.3465 x 0.3465 mm		
	Brightness*1	300cd/ m² typ.		
	Contrast Ratio*1	4000:1 typ.		
	Viewing Angle (H/V)	176°/176° (CR≥10)		
	Active Screen Area (W x H)	(Approx.) 1330.6 × 748.4 mm (42.386"x 29.465")		
	Response Time	8.8 ms (gray to gray, avg.)		
	Backlight	LED, direct type		
Input Terminal*3		$HDMI^{TM*4} \times 3$, RCA video $\times 1$, RCA L/R $\times 1$, Antenna (DIN type) $\times 1$		


Output Terminal*3		Digital audio output x1, USB power supply x 1, Φ 3.5mm audio out (headphone) x 1,
Input/Output Terminal*3		LAN port, USB x 1, Service only (\oplus 3.5 mm jack)
Mounting		VESA (4 points)*5300 x 200 mm pitch
Power supply		110V - 240V AC, 50/60Hz
Power Consumption		185 W
AC cord		3m
Environmental	Operating Temperature	0°C to 40°C *7
Conditions	Operating Humidity	20% to 80% RH (no condensation)
Dimensions*6 (W x D x H) (without Stand)		1358 x 300 x 864 mm (1358 x 83 x 790 mm)
Weight (w/o stand)		18.5 kg (17.5 kg)
Main Accessories		Remote controller x 1, AAA manganese battery x 2 , Stand x 1 set, HDMI locking clamp x 3, USB locking wire x 5
Option (sold separately)		AN-MMSTP1 / FS2B2

*1 Brightness and contrast ratio depend on input mode and other picture settings. Brightness level will decrease slightly over the lifetime of the product. Due to the physical limitations of the equipment, it is not possible to maintain a precisely constant level of brightness. *2 OSD menu does not rotate. Remains landscape position. *3 Use a commercially available connection cable for PC and other video connections. *4 For both PC and AV components. *5 To use the VESA-standard mounting bracket, use M6 screws that are 8 to 10mm plus the thickness of the bracket. *6 Display only, not including protrusions. *7 When using portrait condition, keep it within +/- 20 degrees. When using Multi-monitor and portrait condition, these operating temperature: 0 to 35°C."

Dimensions/Weight (1unit)

	(w/ Stand)	(w/o Stand)
Dimensions (W x H x D) (mm)	1,358 x 864 x 300	1.358 x 790 x 83
Weight (kg)	18.5	17.5






Terminals



- 1 Antenna 2 USB Port (Power Supply)
- ③ USB Port (2.0)
- 4 HDMI 1
- 5 HDMI 2
- (6) HDMI 3
- (7) Headphone/Audio Out(L/R)
- 8 Digital Audio Output
- (10) AV IN (Video, L/R)
- (11) Service Only (RS232C input*) *Required RS232C converter


Dimensions/Weight (4unit)

Dimensions (W x H x D) (mm)	2718 X 2266 (max) x 950
Weight (kg) approx.	117



Dimensions/Weight (Multi-monitor Floor stand)

Dimensions (W x H x D) (mm)	1010~1970) x (1670~1970) x 950
Weight (kg) approx.	43



2x2 Multi-monitor Floor stand FS2B2 (supplied by Eagle Mount)

Design and Specifications are current as of July 2020, but subject to change without prior notice. Actual colours may differ slightly in this catalogue. For details, please consult with SHARP Service center, your local authorized Sharp dealer or representative.

SHARP

SHARP ELECTRONICS (MALAYSIA) SDN. BHD. (No.356997-H)

No.1A, Persiaran Kuala Langat, Section 27, 40400 Shah Alam, Selangor Darul Ehsan. Product Enquiry: 03 5102 5369 Service Enquiry: 1 800 888 678 (Toll Free)

Email: productinfo@my.sharp-world.com

🜀 🚹 Sharp Malaysia | my.sharp



SHARP BIG AQUOS

Multi-Monitor For All Your Business Needs



MESMERISE YOUR SENSES WITH A STUNNING VISUAL EXPERIENCE


BIG AQUOS

LARGE, HIGH-QUALITY 4K SCREENS GREATER VISUAL DETAILS, MORE VIVID COLOURS










► HIGH QUALITY 4K DISPLAY

Up-converts from HD/2K sources to 4K. Contrast and colour are optimised for best experience.



► VIVID COLOUR DISPLAY


Visual display made more stunning with 16.77 million colours in 3840 x 2160 pixels in a 60-inch monitor.



• Contents displayed and player are not included in the product • Equipment for video conferencing is not included • Sold separately: Multi-monitor Floor Stand (FS2B2)

MASSIVE 120-INCH DISPLAY

Install the 120-inch easily and double the size of your display while capturing every detail, beautifully.



MADE IN JAPAN PANEL

The panel is assembled in Japan with quality assured. It has passed over 7 rigorous tests conducted on it.



7 Shields Protection

All SHARP products have passed strict Japanese quality standards. SHARP TVs have been proven to operate safely and are highly durable under various circumstances.

PRESENTATION MADE EASY WITH **SUPERB FEATURES**

AUTO CONTENT MANAGEMENT

Show customers your best offers at your preferred time to maximise impact and interest. Via the single TV set function, the content display times can be pre-set in advance. For multi-monitors, no advance pre-set time feature is available.




VARIOUS SOLUTIONS FOR DIFFERENT BUSINESS NEEDS

Four split screens can be combined into one image on this Multi-monitor, with the **Multi-monitor Setting Tool.**



WELCOME



HOTELS

Big-screen clarity for the convenience of guests

Keep guests well-informed throughout the hotel area with the latest news and updates, with Sharp's large screen, brilliant monitor.

EVENTS

Maximise your engagement with patrons

BATIK EXPO

Ensure your events are a success with large monitors that showcase content in an exciting way.

EDUCATION

Large screens provide greater details for ease of teaching

Capture the attention of students with large screens that present information in an easily-understood, interesting manner.



MALLS & RETAIL SHOPS Large screens attract and hold the attention of shoppers

Sharp's high-quality screens will help you grab the attention of shoppers and delight them with attractive product information.



BUSINESSES

Improve employee engagement and interaction

Enhance communication with your employees with large screens that make meetings and info-sharing more engaging.



GOVERNMENT AGENCIES

Large screens make it easier to provide vital information to the public

Sharp's brilliant, big screens enable important information to be conveyed to the public in an effective, eye-catching way.

EASY SET-UP FOR MAXIMUM EXPOSURI



AMAZE YOUR CLIENTS WITH THE EXTRA-LARGE, BRILLIANT DISPLAY WITH A PORTABLE STAND

Set up Sharp's large monitor with ease, at your events and meetings. The angle of the monitor can be adjusted quickly and easily according to your preference, for maximum exposure.





CONVENIENT ASSIST FOR SETTINGS/ADJUSTMENTS

The Multi-monitor Setting Tool helps you set up and adjust the gap parity among the Multi-monitors.





MULTI-MONITOR COMBINATION

Flexible installment with less investment-Portrait to Multi-monitor.

1-1	
1-2	

<u> </u>	2 X 1	
-1	1-1	2-1
-2	2 X 2	
	1-1	2-1
	1-2	2-2

1-1 2-1

1-2 2-2 1-3 2-3

3 X 1 1-1 2-1 3-1

3 X 2 1-1 2-1 3-1 1-2 2-2 3-2 1 X 3


Retractable Locking Caster Wheels

> 1-1 1-2 1-3


3 X 3 1-1 2-1 3-1 1-2 2-2 3-2 2-3 1-3 3-3




WiFi (wireless)



*Requires a RS-232C converter







Just set up Sharp's Big-Screen Monitor once, and save to your USB. You can then set up as many large screens as you like by simply plugging in the USB. There is no need to set up the monitors one by one using the remote control.

CONVENIENT TOOLS FOR BUSINESS USE

USB LOCKING WIRE PREVENTS USB THEFT

A USB locking wire ensures that your device stays in place and will not be accidentally dislodged. Importantly, it prevents USB theft.

USB locking wire prevents USB theft






PREVENT HDMI DISCONNECTION

Ensure no interruption to your video and audio signals for a smooth and continuous picture display and sound output. A HDMI locking clamp prevents HDMI disconnection.

HDMI locking clamp prevents HDMI disconnection





SETTING UP THE DISPLAY

Detachable LED lens

CP1X has a pop-out LED lens to receive signals, better.





